

Product Data Sheet



PA 430/5

EAN 4047526023331

ID 23333

Hub fitting wheel with pneumatic tyres, with pressed steel rim

Wheels:

Pneumatic tyre with tube, outstandingly high operational comfort, exceptionally high floor preservation, PAH conform acc. to EU directive 2005/69/EC.

Tread colours: black

Wheel centre/rim:

Pressed steel rim, with central hole, fixing holes are countersunk for mounting on conventional hub flanges, lacquered. Tyre mounted on rim.

Wheel centre colour: blue passivated



Rolling resistance

■ ■ ■ □ □ Good

Operating noise

■ ■ ■ ■ ■ Excellent

Floor surface preservation

■ ■ ■ ■ ■ Excellent

Product Data Sheet



Technical data

Profile		Blockprofil
Bolt hole Ø		16,5
Wheel Ø		420 mm (D)
Tyre width		115 mm (T2)
Tyre dimension		4.00-8
Ply rating		6
Load cap. at 4 km/h		650 kg
No. of fixing holes		5
Tyre pressure		7,0/101 bar/psi
Central hole Ø		82 mm (d)
PCD		130 mm (d1)
Profile ribbed profile		B08
unit weight		7,1 kg
Temperature resistance to		-30 ° C
Temperature resistance to		50 ° C
tread and tyre hardness		65° Shore A
Bearing type		Flange

