

Product Data Sheet



P 265/20-75R

EAN 4047526254698

ID 254698

Wheel with pneumatic tyres, with pressed steel rim

Wheels:

Pneumatic tyre with tube, outstandingly high operational comfort, exceptionally high floor preservation, PAH conform acc. to EU directive 2005/69/EC.

Tread colours: black

Wheel centre/rim:

Made of pressed steel, with tubular steel hub, zinc-plated, blue-passivated, Cr6-free. Tyre mounted on rim.

Wheel centre colour: silver



Rolling resistance

■ ■ ■ □ □ Good

Operating noise

■ ■ ■ ■ ■ Excellent

Floor surface preservation


■ ■ ■ ■ ■ Excellent

Product Data Sheet



Technical data

Profile		Rillenprofil
Wheel Ø		260 mm (D)
Tyre width		85 mm (T2)
Tyre dimension		3.00-4
Ply rating		4
Load cap. at 4 km/h		250 kg
Tyre pressure		3,5/50 bar/psi
Axle bore Ø		20 mm (d)
Hub length		75 mm (T1)
Profile ribbed profile		R01
unit weight		1,6 kg
Temperature resistance to		-25 ° C
Temperature resistance to		50 ° C
tread and tyre hardness		60° Shore A
Bearing type		Roller bearing



Product Data Sheet



Variants



P 265/20-75R-SG

Wheel with pneumatic tyres, with pressed steel rim