

# Product Data Sheet



## PS 310/25-75K

EAN 4047526257453

ID 257451

### Heavy duty wheel with pneumatic tyres

#### Wheels:

Pneumatic tyre with tube, outstandingly high operational comfort, exceptionally high floor preservation, PAH conform acc. to EU directive 2005/69/EC.

**Tread colours:** black

#### Wheel centre/rim:

Pressed steel rim, pressed and bolted, with welded tubular steel hub, zinc-plated, blue-passivated, Cr6-free.

**Wheel centre colour:** blue passivated



#### Rolling resistance

■ ■ ■ □ □ Good

#### Operating noise

■ ■ ■ ■ ■ Excellent














#### Floor surface preservation

■ ■ ■ ■ ■ Excellent

# Product Data Sheet



## Technical data

Profile		Blockprofil
Wheel Ø		300 mm (D)
Tyre width		100 mm (T2)
Tyre dimension		4.00-4
Ply rating		6
Load cap. at 4 km/h		450 kg
Tyre pressure		7,5/110 bar/psi
Axle bore Ø		25 mm (d)
Hub length		75 mm (T1)
Profile ribbed profile		B02
unit weight		3,2 kg
Temperature resistance to		-25 ° C
Temperature resistance to		50 ° C
tread and tyre hardness		65° Shore A
Bearing type		Ball bearing

