

Product Data Sheet



PS 464/30-90K

EAN 4047526257590

ID 257592

Heavy duty wheel with pneumatic tyres

Wheels:

Pneumatic tyre with tube, outstandingly high operational comfort, exceptionally high floor preservation, PAH conform acc. to EU directive 2005/69/EC.

Tread colours: black

Wheel centre/rim:

Pressed steel rim, pressed and bolted, with welded tubular steel hub, zinc-plated, blue-passivated, Cr6-free.

Wheel centre colour: blue passivated



Rolling resistance

■ ■ ■ □ □ Good

Operating noise

■ ■ ■ ■ ■ Excellent














Floor surface preservation

■ ■ ■ ■ ■ Excellent

Product Data Sheet



Technical data

Profile		Blockprofil
Wheel Ø		460 mm (D)
Tyre width		145 mm (T2)
Tyre dimension		5.00-8
Ply rating		8
Load cap. at 4 km/h		1140 kg
Tyre pressure		7,0/101 bar/psi
Axle bore Ø		30 mm (d)
Hub length		90 mm (T1)
Profile ribbed profile		B08
unit weight		10,5 kg
Temperature resistance to		-25 ° C
Temperature resistance to		50 ° C
tread and tyre hardness		65° Shore A
Bearing type		Ball bearing

