

# Product Data Sheet



## L-POEV 125K-FI-SG

EAN 4047526272104

ID 272104

**Pressed steel swivel castor, medium heavy duty brackets, with top plate fitting and 'stop-fix' brake, Heavy duty wheel with elastic solid rubber tyres 'Blickle EasyRoll', with nylon wheel centre, non-marking**

### Bracket:

Made of pressed steel, with double ball bearing in the swivel head, ball protection by the special top plate and ball disc design. The special Blickle dynamic riveting process of the swivel head results in minimal swivel head play and smooth rolling characteristics with an increased service life achieved by the work hardening of the ball race grooves. Bolted wheel axle. Zinc-plated, blue-passivated, Cr6-free.

### Wheels:

Made of high-quality elastic solid rubber, in smooth rolling quality "Blickle EasyRoll", very high operational comfort, low-noise operation, low rolling resistance, very good floor preservation, vulcanised on the wheel centre.

**Tread colours:** grey

### Wheel centre/rim:

Made of high-quality, impact-resistant nylon. Vulcanised tyre.

**Wheel centre colour:** black

**Variant:** non-marking



### Rolling resistance

■■■■□ Very good

### Operating noise

■■■■□ Very good

### Floor surface preservation

■■■■□ Very good

# Product Data Sheet



## Technical data

Plate size		100 x 85
Bolt hole spacing		80 x 60
Bolt hole Ø		9
Wheel Ø		125 mm (D)
Wheel width		40 mm (T2)
Load capacity		200 kg
Total height		150 mm (H)
Offset swivel castor		40 mm
unit weight		1,1 kg
Temperature resistance to		-25 ° C
Temperature resistance to		80 ° C
tread and tyre hardness		65° Shore A
Bearing type		Ball bearing

