

Product Data Sheet



LPA-VPA 75K-FI-FA

EAN 4047526273736

ID 273730

Light duty swivel castor with top plate fitting with synthetic brake lever, Wheel with solid rubber tyres, with synthetic rim

Bracket:

Made of pressed steel, with double ball bearing in the swivel head, ball protection by the special top plate and ball disc design. The special Blickle dynamic riveting process of the swivel head results in minimal swivel head play and smooth rolling characteristics with an increased service life achieved by the work hardening of the ball race grooves. Bolted wheel axle. Zinc-plated, blue-passivated, Cr6-free.

Wheels:

Made of high-quality solid rubber, very high operational comfort, low-noise operation, very good floor preservation.

Tread colours: dark grey

Wheel centre/rim:

Made of high-quality, impact-resistant nylon. Pressed-on tyre.

Wheel centre colour: black



Rolling resistance

■ ■ ■ □ □ Good

Operating noise

■ ■ ■ ■ □ Very good









Floor surface preservation

■ ■ ■ ■ □ Very good

Product Data Sheet



Technical data

Plate size		60 x 60
Bolt hole spacing		38x38/48x48
Bolt hole Ø		6,2
Wheel Ø		75 mm (D)
Wheel width		25 mm (T2)
Load capacity		60 kg
Total height		100 mm (H)
Offset swivel castor		29 mm
unit weight		0,4 kg
Temperature resistance to		-20 ° C
Temperature resistance to		60 ° C
tread and tyre hardness		80° Shore A
Bearing type		Ball bearing

