Product Data Sheet



LH-SP0 125K-1-ST

EAN 4047526278977

ID 278978

Pressed steel swivel castor, heavy duty castors, with top plate fitting and 'stop-top' brake, Heavy duty nylon wheel

Bracket:

Made of heavy pressed steel, with heavy fork and top plate, very strong bolted and secured central kingpin, double ball bearing in the swivel head, additionally reinforced by the integration of four specially shaped and hardened bearing seats resulting in a very high resistance to shock and impact loads. Bolted wheel axle. Bolted wheel axle. Zincplated, blue-passivated, Cr6-free.



Made of high-quality, impact-resistant nylon, very rugged, heavy wheel design, very low rolling and swivelling resistance, smooth running performance on even floors, very high abrasion resistance.

Tread colours: natural white

Wheel centre/rim: - Wheel centre colour: natural white



Rolling resistance

Excellent

Operating noise

■■□□□ Satisfactory

Floor surface preservation

Satisfactory

Product Data Sheet

Blickle

Technical data

Plate size		100 x 85
Bolt hole spacing		80 x 60
Bolt hole Ø	7	9
Wheel Ø	©	125 mm (D)
Wheel width	, Ū₄	40 mm (T2)
Load capacity	ä	700 kg
Total height	<u> Z</u>	165 mm (H)
Offset swivel castor	ð	45 mm
unit weight	Ø	2,2 kg
Temperature resistance to	J.	-25 ° C
Temperature resistance to	J.	80 ° C
tread and tyre hardness		70° Shore D
Bearing type	•	Ball bearing

