

Product Data Sheet



L-PO 75R-FI

EAN 4047526295622

ID 295626

Pressed steel swivel castor, medium heavy duty brackets, with top plate fitting an 'stop-fix' brake, Nylon wheel

Bracket:

Made of pressed steel, with double ball bearing in the swivel head, strong central kingpin ball protection by the special top plate and ball disc design. The special Blickle dynamic riveting process of the swivel head results in minimal swivel head play and smooth rollin characteristics with an increased service life achieved by the work hardening of the ball race grooves. Bolted wheel axle. Zinc-plated, blue-passivated, Cr6-free.

Wheels: Made of high-quality, impact-resistant nylon. **Tread colours:**

natural white

Wheel centre/rim: - Wheel centre colour: natural white



Rolling resistance

■■■■■ Excellent

Operating noise

■■□□□ Satisfactory

Floor surface preservation

■■□□□ Satisfactory

Product Data Sheet



Technical data

Plate size		100 x 85
Bolt hole spacing		80 x 60
Bolt hole Ø		9
Wheel Ø		75 mm (D)
Wheel width		32 mm (T2)
Load capacity		200 kg
Total height		100 mm (H)
Offset swivel castor		38 mm
unit weight		0,7 kg
Temperature resistance to		-25 ° C
Temperature resistance to		80 ° C
tread and tyre hardness		70° Shore D
Bearing type		Roller bearing

