

LONGRUN®

Digital MIG/ TIG/STICK Welder



350LCT



500LCT



CO₂/MIG WELDER (GMAW)

▪ Specifications

Input voltage (V, PH)			220, 1/3			380, 1/3			220, 1/3			380, 1/3			
Process	DC TIG	CO ₂	STICK	DC TIG	CO ₂ /MAG	STICK	DC TIG	CO ₂ /MAG	STICK	DC TIG	CO ₂ /MAG	STICK	DC TIG	CO ₂ /MAG	
Input capacity (kVA)	11	18	15	10	17	14	18	25.1	14	17	24.5	13.5			
Open circuit voltage (V)	72	70	81	68	67	71	72	70	81	70	68	78			
Output current (A)	10~350	50~350	10~350	10~350	50~350	10~350	10~500	50~500	10~350	10~500	50~500	10~350			
Duty cycle (%)	60			60			60			60					
Dimension (mm)	416 X 788 X 694			416 X 788 X 694			416 X 788 X 694			416 X 788 X 694					
Weight (kg)	82			82			84			84					

Function

- Multi Process Welding (TIG-DC, MIG/MAG, STICK-DC)
- All welding process is possible after one installation
- Stable welding quality by Full digital control
- Memory function
- Low spatters and stable welding start by start control technology
- Optimized for educational purpose at Welding Institution



- Multi Process Welding (TIG-DC, MIG/MAG, STICK-DC)
- All welding process is possible after one installation
- Stable welding quality by Full digital control
- Memory function
- Low spatters and stable welding start by start control technology
- Optimized for multi purpose welding and automation welding

