

Digital Multi Process Welder



350PMA



500PMA



Specifications

Input voltage (V, Ph)	220, 1/3			380, 1/3		
	AC/DC TIG	CO2	STICK	AC/DC TIG	CO2	STICK
Input capacity (kVA)	11	18	15	10	17	14
Open circuit voltage (V)	72	70	81	68	67	71
Output current (A)	10~350	50~350	10~350	10~350	50~350	10~350
Duty cycle (%)	60					
Dimension (mm)	416 X 694 X 788					
Weight (kg)	83					

Function

- Multi Process Welding (TIG-AC/DC, MIG/MAG, STICK-AC/DC)
- Full digital control and user friendly interface
- All welding process is possible after one installation
- Optimized for educational purpose at Welding Institution



Input voltage (V, Ph)	220, 1/3			380, 1/3		
	AC/DC TIG	CO2	STICK	AC/DC TIG	CO2	STICK
Input capacity (kVA)	18	25.1	14	17	24.5	13.5
Open circuit voltage (V)	72	70	81	70	68	78
Output current (A)	10~500	50~500	10~350	10~500	50~500	10~350
Duty cycle (%)	60					
Dimension (mm)	416 X 694 X 788					
Weight (kg)	85					

- Multi Process Welding (TIG-AC/DC, MIG/MAG, STICK-AC/DC)
- Full digital control and user friendly interface
- All welding process is possible after one installation
- Optimized for educational purpose at Welding Institution

