Product Data Sheet



LS-SVS 201K

EAN 4047526614010

ID 614016

Welded steel heavy duty swivel castor, strong swivel head design, Extra heavy duty solid steel wheel

Bracket:

Particularly rugged welded steel construction, with axial grooved ball bearing DIN 711 and tapered roller bearing DIN 720 in the swivel head, dust and splash-proof, fitted grease nipple, bolted and secured with a welded very strong central kingpin. Bolted wheel axle. Zinc-plated, yellow-passivated, Cr6-free.

Wheels:

Made of mild steel, with slightly crowned tread and lightly oiled surface, very low rolling and swivelling resistance, smooth running performance on even floors, extremely wear-resistant, particularly high static and dynamic load capacity.

Tread colours: silver

Wheel centre/rim: - Wheel centre colour: silver






Product Data Sheet

Blickle

Technical data

Plate size		175 x 140
Bolt hole spacing		140 x 105
Bolt hole Ø	鬥	14
Wheel Ø	©	200 mm (D)
Wheel width	, []₄	55 mm (T2)
Load capacity	ධි	3000 kg
Total height	Ą	255 mm (H)
Offset swivel castor	ð	65 mm
unit weight	Ø	18,9 kg
Temperature resistance to	J.	-25 ° C
Temperature resistance to	J.	120 ° C
tread and tyre hardness		190 - 230 HB
Bearing type	•	Ball bearing



Product Data Sheet



Variants



LS-SVS 201K-RI2

Welded steel heavy duty swivel castor, strong swivel head design, Extra heavy duty solid steel wheel



LS-SVS 201K-RI4

Welded steel heavy duty swivel castor, strong swivel head design, Extra heavy duty solid steel wheel