

Product Data Sheet



LO-ALEV 127K-SG

EAN 4047526636418

ID 636415

Welded steel heavy duty swivel castor, Heavy duty wheel with elastic solid rubber tyres 'Blickle EasyRoll', with aluminium wheel centre, non-marking

Bracket:

Sturdy welded steel construction, with double ball bearing in the swivel head, additionally reinforced by the integration of four specially shaped and hardened bearing seats, swivel head seal with labyrinth design, fitted grease nipple, bolted and secured with a welded very strong central kingpin. Bolted wheel axle. Zinc-plated, blue-passivated, Cr6-free.

Wheels:

Made of high-quality elastic solid rubber, in smooth rolling quality "Blickle EasyRoll", very high operational comfort, low-noise operation, low rolling resistance, very good floor preservation, vulcanised on the wheel centre.

Tread colours: grey

Wheel centre/rim: Made of die-cast aluminium. Vulcanised tyre.

Wheel centre colour: silver grey

Variant: non-marking



Rolling resistance

■■■■□ Very good

Operating noise

■■■■□ Very good

Floor surface preservation

■■■■□ Very good

Product Data Sheet



Technical data

Plate size		140 x 110
Bolt hole spacing		105 x 75-80
Bolt hole Ø		11
Wheel Ø		125 mm (D)
Wheel width		50 mm (T2)
Load capacity		270 kg
Total height		170 mm (H)
Offset swivel castor		50 mm
unit weight		3,8 kg
Temperature resistance to		-25 ° C
Temperature resistance to		80 ° C
tread and tyre hardness		65° Shore A
Bearing type		Ball bearing

