

Product Data Sheet



LK-POEV 125K-1-FI-SG

EAN 4047526646653

ID 646653

Pressed steel swivel castor, medium heavy duty brackets, with top plate fitting and 'stop-fix' brake, Heavy duty wheel with elastic solid rubber tyres 'Blickle EasyRoll', with nylon wheel centre, non-marking

Bracket:

Made of heavy pressed steel, swivel bracket with double ball bearing in the swivel head, swivel head seals. The special Blickle dynamic riveting process of the swivel head results in minimal swivel head play and smooth rolling characteristics with an increased service life achieved by the work hardening of the ball race grooves. Bolted wheel axle. Zinc-plated, blue-passivated, Cr6-free.

Wheels:

Made of high-quality elastic solid rubber, in smooth rolling quality "Blickle EasyRoll", very high operational comfort, low-noise operation, low rolling resistance, very good floor preservation, vulcanised on the wheel centre.

Tread colours: grey

Wheel centre/rim:

Made of high-quality, impact-resistant nylon. Vulcanised tyre.

Wheel centre colour: black

Variant: non-marking



Rolling resistance

■■■■□ Very good

Operating noise

■■■■□ Very good







Floor surface preservation

■■■■□ Very good

Product Data Sheet



Technical data

Plate size		100 x 85
Bolt hole spacing		80 x 60
Bolt hole Ø		9
Wheel Ø		125 mm (D)
Wheel width		40 mm (T2)
Load capacity		250 kg
Total height		155 mm (H)
Offset swivel castor		48 mm
unit weight		1,4 kg
Temperature resistance to		-25 ° C
Temperature resistance to		80 ° C
tread and tyre hardness		65° Shore A
Bearing type		Ball bearing

