

Product Data Sheet



LWK-TPA 126K-FI-FK-ZA58

EAN 4047526063115

ID 742077

Synthetic swivel castor Blickle WAVE with stem fitting and 'stop-fix' brake, Wheel with thermoplastic rubber tread, with polypropylene wheel centre

Bracket:

Made of high-quality, impact-resistant and reinforced nylon, with encapsulated, double-sealed grooved ball bearing in the swivel head, with zinc-plated, blue-passivated bolted and secured steel plug-in stem fitting (Cr6-free). Modern, shapely design.

Wheels:

Made of high-quality thermoplastic rubber elastomer (TPE), high operational comfort, low-noise operation, low rolling and swivelling resistance, good floor preservation, chemically bonded for an inseparable connection to the wheel centre.

Tread colours: grey

Wheel centre/rim:

Made of high-quality, impact-resistant polypropylene. Chemically bonded.

Wheel centre colour: grey



Rolling resistance

■■■■□ Very good

Operating noise

■■■■□ Good

Floor surface preservation

■■■■□ Good

Product Data Sheet



Technical data

Wheel Ø		125 mm (D)
Wheel width		32 mm (T2)
Load capacity		110 kg
Total height		160 mm (H)
Stem Ø		27,5 mm
Stem length		45 mm
Ø retaining hole		M8
Position retaining hole		20 mm (H)
Offset swivel castor		40 mm
unit weight		0,8 kg
Temperature resistance to		-20 ° C
Temperature resistance to		60 ° C
tread and tyre hardness		85° Shore A
Bearing type		Ball bearing

