

# Product Data Sheet



## LWK-TPA 101K-FI-FK

EAN 4047526061074

ID 743075

**Synthetic swivel castor Blickle WAVE with bolt hole fitting and 'stop-fix' brake, Wheel with thermoplastic rubber tread, with polypropylene wheel centre**

### Bracket:

Made of high-quality, impact-resistant and reinforced nylon, with encapsulated, double-sealed grooved ball bearing in the swivel head, with bolt hole fitting. Modern, shapely design.

### Wheels:

Made of high-quality thermoplastic rubber elastomer (TPE), high operational comfort, low-noise operation, low rolling and swivelling resistance, good floor preservation, chemically bonded for an inseparable connection to the wheel centre.

**Tread colours:** grey

### Wheel centre/rim:

Made of high-quality, impact-resistant polypropylene. Chemically bonded.

**Wheel centre colour:** grey



### Rolling resistance

■ ■ ■ ■ □ Very good

### Operating noise

■ ■ ■ □ □ Good











### Floor surface preservation

■ ■ ■ □ □ Good

# Product Data Sheet



## Technical data

Plate size		55
Bolt hole Ø		13
Wheel Ø		100 mm (D)
Wheel width		32 mm (T2)
Load capacity		100 kg
Total height		135 mm (H)
Offset swivel castor		38 mm
unit weight		0,5 kg
Temperature resistance to		-20 ° C
Temperature resistance to		60 ° C
tread and tyre hardness		85° Shore A
Bearing type		Ball bearing

