

# Product Data Sheet



## LPA-PATH 50G-FI

EAN 4047526105938

ID 757086

**Light duty swivel castor with top plate fitting with synthetic brake lever, Wheel with thermoplastic polyurethane tread, with nylon wheel centre**

### Bracket:

Made of pressed steel, with double ball bearing in the swivel head, ball protection by the special top plate and ball disc design. The special Blickle dynamic riveting process of the swivel head results in minimal swivel head play and smooth rolling characteristics with an increased service life achieved by the work hardening of the ball race grooves. Bolted wheel axle. Zinc-plated, blue-passivated, Cr6-free.

### Wheels:

Made of high-quality thermoplastic polyurethane, low-noise operation, low rolling and swivelling resistance, good floor preservation, very high abrasion resistance, chemically bonded for an inseparable connection to the wheel centre.

**Tread colours:** dark grey

### Wheel centre/rim:

Made of high-quality, impact-resistant nylon. Chemically bonded.

**Wheel centre colour:** grey



### Rolling resistance

■ ■ ■ ■ □ Very good

### Operating noise

■ ■ ■ ■ □ Good

### Floor surface preservation

■ ■ ■ ■ □ Good

# Product Data Sheet



## Technical data

|                           |  |             |
|---------------------------|--|-------------|
| Plate size                |  | 60 x 60     |
| Bolt hole spacing         |  | 38x38/48x48 |
| Bolt hole Ø               |  | 6,2         |
| Wheel Ø                   |  | 50 mm (D)   |
| Wheel width               |  | 19 mm (T2)  |
| Load capacity             |  | 75 kg       |
| Total height              |  | 71 mm (H)   |
| Offset swivel castor      |  | 25 mm       |
| unit weight               |  | 0,2 kg      |
| Temperature resistance to |  | -25 ° C     |
| Temperature resistance to |  | 70 ° C      |
| tread and tyre hardness   |  | 94° Shore A |
| Bearing type              |  | Plain bore  |

