

# Product Data Sheet



## LPA-PATH 50K-FI-FK

EAN 4047526117788

ID 757087

**Light duty swivel castor with top plate fitting with synthetic brake lever, Wheel with thermoplastic polyurethane tread, with nylon wheel centre**

### Bracket:

Made of pressed steel, with double ball bearing in the swivel head, ball protection by the special top plate and ball disc design. The special Blickle dynamic riveting process of the swivel head results in minimal swivel head play and smooth rolling characteristics with an increased service life achieved by the work hardening of the ball race grooves. Bolted wheel axle. Zinc-plated, blue-passivated, Cr6-free.

### Wheels:

Made of high-quality thermoplastic polyurethane, low-noise operation, low rolling and swivelling resistance, good floor preservation, very high abrasion resistance, chemically bonded for an inseparable connection to the wheel centre.

**Tread colours:** dark grey

### Wheel centre/rim:

Made of high-quality, impact-resistant nylon. Chemically bonded.

**Wheel centre colour:** grey



### Rolling resistance

■■■■□ Very good

### Operating noise

■■■■□ Good

### Floor surface preservation

■■■■□ Good

# Product Data Sheet



## Technical data

Plate size		60 x 60
Bolt hole spacing		38x38/48x48
Bolt hole Ø		6,2
Wheel Ø		50 mm (D)
Wheel width		19 mm (T2)
Load capacity		75 kg
Total height		71 mm (H)
Offset swivel castor		25 mm
unit weight		0,2 kg
Temperature resistance to		-25 ° C
Temperature resistance to		70 ° C
tread and tyre hardness		94° Shore A
Bearing type		Ball bearing

