

Product Data Sheet



LI-VKHT 100G-FI

EAN 4047526122027

ID 763583

Heat-resistant pressed steel swivel castor with top plate fitting and 'stop-fix' brake, Heat-resistant Blickle TempLine® Special wheel with solid rubber tyres, with synthetic rim

Bracket:

Made of pressed steel, with double ball bearing in the swivel head, strong central kingpin, ball protection by the special top plate design. The special Blickle dynamic riveting process of the swivel head results in smooth rolling characteristics, increased service life and the swivel head play is set specifically for high temperature applications, with special heat-resistant grease, Teflon-coated stainless steel axle tube. Bolted wheel axle. Zinc-plated, blue-passivated, Cr6-free.

Wheels:

Made of heat-resistant solid rubber, low-noise operation, good floor preservation, high tear resistance, PAH conform acc. to EU directive 2005/69/EC.

Tread colours: black

Wheel centre/rim:

Made of high-quality, impact-resistant nylon. Heat-resistant. Pressed-on tyre.

Wheel centre colour: black



Rolling resistance

■ ■ ■ □ □ Good

Operating noise

■ ■ ■ □ □ Good

Floor surface preservation

■ ■ ■ □ □ Good

Product Data Sheet



Technical data

Plate size		100 x 85
Bolt hole spacing		80 x 60
Bolt hole Ø		9
Wheel Ø		100 mm (D)
Wheel width		30 mm (T2)
Load capacity		100 kg
Total height		125 mm (H)
Offset swivel castor		36 mm
unit weight		0,8 kg
Temperature resistance to		-30 ° C
Temperature resistance to		260 ° C
tread and tyre hardness		85° Shore A
Bearing type		Plain bore

