

Product Data Sheet



B-GEV 160K-TB-SG

EAN 4047526122966

ID 842745

Fixed castor with drum brake, Heavy duty wheel with elastic solid rubber tyres, with cast iron wheel centre, non-marking

Bracket:

Made of pressed steel. Bolted wheel axle. Zinc-plated, blue-passivated, Cr6-free.

Wheels:

Made of high-quality elastic solid rubber, in smooth rolling quality, steel-wire reinforced, very high operational comfort, low-noise operation, low rolling resistance, very good floor preservation.

Tread colours: black

Wheel centre/rim:

Made of grey cast iron, with grease nipple, lacquered. Steel-wire reinforced tyre, pressed-on.

Wheel centre colour: anthracite

Variant: non-marking



Rolling resistance

■■■■□ Very good

Operating noise

■■■■□ Very good

Floor surface preservation

■■■■□ Very good

Product Data Sheet



Technical data

| | | |
|---------------------------|--|--------------|
| Plate size | | 140 x 110 |
| Bolt hole spacing | | 105 x 75-80 |
| Bolt hole Ø | | 11 |
| Wheel Ø | | 160 mm (D) |
| Wheel width | | 50 mm (T2) |
| Load capacity | | 450 kg |
| Total height | | 195 mm (H) |
| unit weight | | 3,7 kg |
| Temperature resistance to | | -25 ° C |
| Temperature resistance to | | 80 ° C |
| tread and tyre hardness | | 65° Shore A |
| Bearing type | | Ball bearing |

