

Product Data Sheet



LHD-ALEV 125K-SG

EAN 4047526187439

ID 852078

Pressed steel extra heavy duty twin wheel swivel castor, with top plate fitting, Heavy duty wheel with elastic solid rubber tyres 'Blickle EasyRoll', with aluminium wheel centre, non-marking

Bracket:

Made of heavy pressed steel, with heavy fork and top plate, very strong bolted and secured central kingpin, double ball bearing in the swivel head, additionally reinforced by the integration of four specially shaped and hardened bearing seats resulting in a very high resistance to shock and impact loads.

Wheels:

Made of high-quality elastic solid rubber, in smooth rolling quality "Blickle EasyRoll", very high operational comfort, low-noise operation, low rolling resistance, very good floor preservation, vulcanised on the wheel centre.

Tread colours: grey

Wheel centre/rim: Made of die-cast aluminium. Vulcanised tyre.

Wheel centre colour: silver grey

Variant: non-marking



Rolling resistance

■■■■□ Very good

Operating noise

■■■■□ Very good

Floor surface preservation

■■■■□ Very good

Product Data Sheet



Technical data

| | | |
|---------------------------|--|----------------|
| Plate size | | 110 x 140 |
| Bolt hole spacing | | 75-80 x 105 |
| Bolt hole Ø | | 11 |
| Wheel Ø | | 125 mm (D) |
| Wheel width | | 2 x 40 mm (T2) |
| Load capacity | | 500 kg |
| Total height | | 170 mm (H) |
| Offset swivel castor | | 50 mm |
| unit weight | | 3,6 kg |
| Temperature resistance to | | -25 ° C |
| Temperature resistance to | | 80 ° C |
| tread and tyre hardness | | 65° Shore A |
| Bearing type | | Ball bearing |

