

# Product Data Sheet



## HRLK-SPO 75G

EAN 4047526216641

ID 853835

**Levelling castor with integrated truck lock and top plate fitting, Heavy duty nylon wheel**

### Bracket:

"Made of heavy pressed steel, with heavy fork and top plate fitting, very strong bolted and secured central kingpin, double ball bearing in the swivel head, additionally reinforced by the integration of four specially shaped and hardened bearing seats resulting in a very high resistance to shock and impact loads. Steel truck lock. Height adjustment with flat spanner. Bolted wheel axle. Zinc-plated, blue-passivated, Cr6-free."

### Wheels:

Made of high-quality, impact-resistant nylon, very rugged, heavy wheel design, very low rolling and swivelling resistance, smooth running performance on even floors, very high abrasion resistance.

**Tread colours:** natural white

**Wheel centre/rim:** - **Wheel centre colour:** natural white



### Rolling resistance

■■■■■ Excellent

### Operating noise

■■□□□ Satisfactory

### Floor surface preservation

■■□□□ Satisfactory

# Product Data Sheet



## Technical data

Plate size		100 x 85
Bolt hole spacing		80 x 60
Bolt hole Ø		9
Wheel Ø		75 mm (D)
Wheel width		32 mm (T2)
Load capacity		300 kg
Total height		118 mm (H)
Max. total height		120 mm (h)
Adjustment range		2 mm (T4)
Offset swivel castor		56 mm
unit weight		1,7 kg
Temperature resistance to		-25 ° C
Temperature resistance to		80 ° C
tread and tyre hardness		70° Shore D
Bearing type		Plain bore

