

# Product Data Sheet



## HRLK-PO 75G

EAN 4047526216634

ID 882391

### Levelling castor with integrated truck lock and top plate fitting, Nylon wheel

#### Bracket:

"Made of heavy pressed steel, with heavy fork and top plate fitting, very strong bolted and secured central kingpin, double ball bearing in the swivel head, additionally reinforced by the integration of four specially shaped and hardened bearing seats resulting in a very high resistance to shock and impact loads. Steel truck lock. Height adjustment with flat spanner. Bolted wheel axle. Zinc-plated, blue-passivated, Cr6-free."

#### Wheels: Made of high-quality, impact-resistant nylon. Tread colours:

natural white

**Wheel centre/rim: - Wheel centre colour:** natural white



#### Rolling resistance

■■■■■ Excellent

#### Operating noise

■■□□□ Satisfactory

#### Floor surface preservation

■■□□□ Satisfactory

# Product Data Sheet



## Technical data

Plate size		100 x 85
Bolt hole spacing		80 x 60
Bolt hole Ø		9
Wheel Ø		75 mm (D)
Wheel width		32 mm (T2)
Load capacity		200 kg
Total height		118 mm (H)
Max. total height		120 mm (h)
Adjustment range		2 mm (T4)
Offset swivel castor		56 mm
unit weight		1,7 kg
Temperature resistance to		-25 ° C
Temperature resistance to		80 ° C
tread and tyre hardness		70° Shore D
Bearing type		Plain bore

