Product Data Sheet



L-ALEV 160K-CS11-SG-AS

EAN -

ID 913156

Pressed steel swivel castor, medium heavy duty brackets, with top plate fitting and central brake 'central-stop', Heavy duty wheel with elastic solid rubber tyres 'Blickle EasyRoll', with aluminium wheel centre

Bracket:

Made of pressed steel, with double ball bearing in the swivel head, ball protection by the special top plate and ball disc design. The special Blickle dynamic riveting process of the swivel head results in minimal swivel head play and smooth rolling characteristics with an increased service life achieved by the work hardening of the ball race grooves. Bolted wheel axle. Zinc-plated, blue-passivated, Cr6-free.



Made of high-quality elastic solid rubber, in smooth rolling quality "Blickle EasyRoll", very high operational comfort, low-noise operation, low rolling resistance, very good floor preservation, vulcanised on the wheel centre.

Tread colours: grey

Wheel centre/rim: Made of die-cast aluminium. Vulcanised tyre.

Wheel centre colour: silver grey

Technical data

Plate size		140 x 110
Bolt hole spacing		105 x 75-80
Bolt hole Ø	7	11
Wheel Ø	\odot	160 mm (D)
Wheel width	₽ Ū•	50 mm (T2)
Load capacity	ä	350 kg
Total height	Ø,	195 mm (H)
Offset swivel castor	3	60 mm
Temperature resistance to		80 ° C
tread and tyre hardness		65° Shore A
Bearing type	•	Ball bearing

