

Product Data Sheet



LK-ALB 150K

EAN -

ID 917425

Pressed steel swivel castor, medium heavy duty brackets, with top plate fitting, Heavy duty wheel with Blickle Besthane® polyurethane tread, with aluminium wheel centre

Bracket:

Made of pressed steel, with double ball bearing in the swivel head, strong central kingpin, ball protection by the special top plate and ball disc design. The special Blickle dynamic riveting process of the swivel head results in minimal swivel head play and smooth rolling characteristics with an increased service life achieved by the work hardening of the ball race grooves. Bolted wheel axle. Zinc-plated, blue-passivated, Cr6-free.

Wheels:

Made of high-quality, reaction-injected polyurethane-elastomer Blickle Besthane®, low-noise operation, low rolling resistance, high dynamic load capacity, good floor preservation, very high abrasion resistance, high cut and tear propagation resistance, very good chemical connection with the wheel centre.

Tread colours: brown

Wheel centre/rim: Made of die-cast aluminium. Casted tread.



Rolling resistance

■■■■■ Excellent

Operating noise

■■■■□ Good












Floor surface preservation

■■■■□ Good

Product Data Sheet



Technical data

| | | |
|---------------------------|---|--------------|
| Plate size |  | 140 x 110 |
| Bolt hole spacing |  | 105 x 75-80 |
| Bolt hole Ø |  | 11 |
| Wheel Ø |  | 150 mm (D) |
| Wheel width |  | 50 mm (T2) |
| Load capacity |  | 500 kg |
| Total height |  | 197 mm (H) |
| Bolt diameter | | 11 mm |
| Offset swivel castor |  | 63 mm |
| Temperature resistance to |  | -25 ° C |
| Temperature resistance to |  | 70 ° C |
| tread and tyre hardness | | 92° Shore A |
| Bearing type |  | Ball bearing |

Product Data Sheet



Variants



LK-ALB 150K-FI

Pressed steel swivel castor, medium heavy duty brackets, with top plate fitting and 'stop-fix' brake, Heavy duty wheel with Blickle Besthane® polyurethane tread, with aluminium wheel centre



LK-ALB 150K-ST

Pressed steel swivel castor, medium heavy duty brackets, with top plate fitting and 'stop-top' brake, Heavy duty wheel with Blickle Besthane® polyurethane tread, with aluminium wheel centre