


ALFRA ROTABEST® – RB 50 B



RB 50 B

Core drill dimensions	Ø 12.0 - 50.0 mm
Cutting depth	50.0 mm
Twist drill	Ø 1.0 bis 16.0 mm with quick-release chuck MT2 up to Ø 20.0 mm with MK 2 DIN 345 direct
Counterboring	Ø 10.0 - 40.0 mm
Tapping	with tapping attachment: M3 - M20
Arbors	MT2
Stroke	190 mm
Height adjustment	100 mm
2-speed gearbox Load speed	1. Step 250 rpm 2. Step 450 rpm
Power consumption	1,200 W
Voltage	230 V 50/60 Hz 110 V 50/60 Hz
Magnetic adhesion strength	12,000 N
Tool force (10 mm)	3,500 N
Magnetic base	92 x 220 mm
Weight	15.0 kg

Gearboxes	
Oil bath gearbox	✓
Slides	
Infinitely adjustable	✓
Self-adjusting guide	✓
Operation	
Soft-touch grips	✓
Ergonomic switch keyboard	✓
Cable length 5 m	✓
Magnet	
Metal rings	✓
Performance and weight optimisation	✓
Made in Germany ✓	

Scope of delivery	
<ul style="list-style-type: none"> • Metal core drill RB 50 B • Incl. coolant system and tool holder with internal cooling • Carrying case • Drill spray • Seat belt • Operating Instructions 	



MADE IN GERMANY



Prod.-No.

ALFRA Rotabest® RB 50 B	230 Volt	18451
ALFRA Rotabest® RB 50 B	110 Volt	18451.110