



SP-500

SPAZERO SP-500 (Antispatter Agent)

Packaging Unit Liquid 18kg/PVC Pail

:

Features

Spatter created when welding makes adverse effects on product finishing and exfoliates coating after product finishing. Sanding, grinding or chisel has been used for removing spatter or unstable anti-adhesive agent has been used. However, SPAZERO became an essential product at the welding workplace where required increasing a productivity through a quality improvement, cost reduction and working environment improvement.

- Temporary anti-rusting effects
- No adverse effects to welding
- Excellent durability and applicability
- No harm to human body
- Low odor and high workability
- Quick drying and high spread

Uses

Antispatter agent only for iron and nonferrous metals

How to Use

- Clean the surface to be applied before use.
- Apply it thinly and evenly by using spray or brush before welding.
- Do welding immediately after apply is no problem. However, it is more effective to do welding after dried somewhat.

Cautions

- Do not use it near fire because it is flammable.
- Use it at the well-ventilated place.
- Keep it in the cool place below 40°C
- After welding, user must have a self-test and then decide to use the product if there is post-processing such as painting. (In case of plating, you go on plating after remove of solvent.

※Please read the product instruction manual and MSDS(Material Safety Date Sheet) before you use the product. Sometimes there would be wrong knowledge on this product, so if there are any questions, please contact us or the store where you purchased it.