



STANDARD SPECIFICATION OF YUKWANG PORTABLE GAS CUTTING MACHINE SERIES

YK-150 / Cuttis




Input Voltage	100/110V 200/220V option
Frequency	50Hz/ 60Hz
Cutting Thickness	6 ~ 50mm
Cutting Speed	100~1000mm/min
Circle Cutting Range in Diameter	360 ~ 1,200mm
Bevel Angle	0° ~ 45°
Dimension (L x W x H)	387 x 123 x 220mm
Weight	8.5kg

YK-300 / Frog




Input Voltage	100/110V 200/220V option
Frequency	50Hz/ 60Hz
Cutting Thickness	6 ~ 50mm
Cutting Speed	100~1000mm/min
Bevel Angle	0° ~ 45°
Loading Capacity	50kg(110lbs)
Dimension (L x W x H)	310 x 450 x 300mm
Weight	12kg

YK-450 / Elephant



Input Voltage	100/110V 200/220V option
Frequency	50Hz/ 60Hz
Cutting Thickness	6 ~ 50mm
Cutting Speed	100~1000mm/min
Cutting Range	By 700mm
Cutting Accuracy	0.5mm over 500mm \varnothing cutting
Motor	DC Motor (5W)
Dimension (H x D)	600 x 500 x 765mm
Weight	33kg

YK-20 / Phoenix



Cutting Thickness	Up to 50mm
Bevel Angle	0° ~ 45°
Pipe Diameter	100~600mm by 2.4m chain over 600mm by extra chain
Tip	121 Type (Acetylene) 122 Type (Propane) 123 Type (Ethylene)
Dimension (L x W x H)	212 x 208 x 415mm
Weight	6.8kg